Multi-Contact MC3 and MC4 connector systems

Multi-Contact AG was founded in 1962 and is currently employing more than 700 staff. All manufacturing sites are ISO 9001-certified and therefore meet the highest quality demands.

MC connector systems

The components of the MC connector system for photovoltaics are designed to allow time-saving and safe serial and parallel wiring of PV modules for building-integrated and free-standing solar installations. For practical use the connector systems MC3 and MC4 are available, depending on the existing modules or inver-ters.

The proven MC3 connector systems

- ⁿ Diameter Ø 3 mm
- Rated current max. 30 A for 6 mm² max. 20 A for < 4 mm²

- ⁿ System voltage max. 1000 V
- Degree of protection, connected IP65
- Protection class II
- ⁿ Temperature range 40°C to +90°C
- ⁿ TÜV Rheinland ⁻ type approved

The interlockable MC4 connector systems

- ⁿ Diameter Ø 4 mm
- ⁿ Rated current max. 30 A
- ⁿ System voltage max. 1000 V
- Degree of protection, connected IP67
- Easy installation
- ⁿ Locking system "Snap in"
- ⁿ Protection class II
- ⁿ Temperature range 40°C to +90°C
- ⁿ TÜV Rheinland type approved



The MC3 plugs and sockets, shown with associated contacts. contacts.

The MC4 plugs and sockets, shown with associated



MultiContact PV-KBT3II | MultiContact PV-KST3II | MultiContact PV Model 7.1 mm)

Description

Warranty

Model

Description

Warranty

Model

Description

Warranty

Female type MC3 for Radox / Draka / Studer 2 years

7.1 mm)
Male type MC3 for
Radox / Draka / Studer 2 years

KBT3/6III (A: 6 mm, D: 6.5 - 9 mm) Female type MC3 for Radox / Draka / Studer 2 years

MultiContact PV-KST3/6III (A: 6 mm², D: 6.5 - 9 mm)
Male type MC3 for
Radox / Draka / Studer 2 years

MultiContact PV-KBT4/6II (A: 4 - 6 mm D: 5.5 - 9 mm) Female type MC4 for Radox / Draka / Studer 4 - 6 mm 2 years



MultiContact PV-KST4/6II (A: 4 - 6 mm², D: 5.5 - 9 mm) Male type MC4 for Radox / Draka / Studer 4 male and female MC3

- 6 mm 2 years

MultiContact PV-R-WZ3 Installation device for

2 years

CZM-19100 crimping pliers insert For MC4 (only use with locator)

MultiContact PV-ES-

2 years



MultiContact PV-CZM-16100A crimping pliers For MC3 (MC4: insert

and locator necessary) 2 years



MultiContact PV-LOC crimping pliers locator

For MC4 (only use with crimping pliers insert)

2 years



MultiContact PV-WZ-AD/GWD MultiContact PV-SSE-AD4

Socket wrench insert for crimping pliers PV-CZM 2 years



Socket wrench insert for crimping pliers PV-CZM 2 years



MultiContact PV-PST test pin

For MC type 4

2 years



MultiContact assembly key PV-MS For MC type 4

2 years



MultiContact PV branch plug Model MC3 PV-AZS3-UR For MC type 3 Description Warranty 2 years




MultiContact PV branch socket MC3 PV-AZB3-UR For MC type 3 2 years




MultiContact PV branch plug MC4 PV-AZS4 For MC type 4




MultiContact PV branch socket MC4 PV-AZB4 For MC type 4



The MC3 plugs are based on contacts with a diameter of 3 mm and comply with protection class IP65.





The interlockable MC4 plugs have contacts with diameters of 4 mm and comply with protection class IP67.